

82302B- NOR - 1/2 Ton High Lift Wheel Dolly



Brand: Norco
Product Code: NOR-82302B
Call for Price: 877-805-1154

Short Description

INTENDED USE:

For the removal and installation of single, tandem and duplex tires and wheels which are mounted on trucks that are supported above ground level.

FEATURES:

- Heavy duty lift arms made with ball bearing conveyer rollers which allow easy rotation of wheels for alignment with bolt pattern.
- 7-1/2" of side to side lift arm adjustment eliminates the trial and error method of aligning the rim's lug holes with the wheel drum.

- A 1,500 pound capacity heavy duty winch with 5 to 1 gear ratio provides ease of operation.
- The winch gear design acts as a brake and allows the load to be lowered incrementally if desired and without the need for constant hand pressure against the crank handle.
- A hydraulic jack tilts the lift arms to match the angle of the spindle.
- Safety chain provided to secure tires and wheels to the dolly.
- Maneuverability is made easy by means of two rear mounted ball bearing caster wheels. The caster wheels include a locking mechanism which can prevent the dolly from moving.

Description

For the removal and installation of single, tandem and duplex tires and wheels which are mounted on trucks that are supported above ground level.

FEATURES:

- Heavy duty lift arms made with ball bearing conveyer rollers which allow easy rotation of wheels for alignment with bolt pattern.
- 7-1/2" of side to side lift arm adjustment eliminates the trial and error method of aligning the rim's lug holes with the wheel drum.
- A 1,500 pound capacity heavy duty winch with 5 to 1 gear ratio provides ease of operation.
- The winch gear design acts as a brake and allows the load to be lowered incrementally if desired and without the need for constant hand pressure against the crank handle.
- A hydraulic jack tilts the lift arms to match the angle of the spindle.
- Safety chain provided to secure tires and wheels to the dolly.
- Maneuverability is made easy by means of two rear mounted ball bearing caster wheels. The caster wheels include a locking mechanism which can prevent the dolly from moving.

Specifications

DIMENSIONS:

Lift Height	
Low	3"
High	41.25"
Lift Arms	
Width	24.25"
Length	21"
Tilt Angle	-2° to +30°
Side to Side Adj.	
Left	3.25"
Right	4.25"
Overall Dimensions	
Length	45.75"
Width	43.75"
Height	62"
Shipping Weight	315 lbs.

PLEASE GIVE US CALL SO WE MAY PROVIDE YOU AN ACURATE SHIPPING QUOTE. AUTOMATED SYSTEM CANNOT PROVIDE ACURATE PRICING FOR SHIPMENTS WEIGHING OVER 100 LBS