925011 - NOR - 200/10,000 PSI Two-Speed Lightweight Hand Pump



Brand: Norco **Product Code:** NOR-925011

Phone: 877-805-1154 - Email: parts@automotive-lift.com

Call for Price: 877-805-1154

Short Description FEATURES:

- 3/8 NPT hose connection on all pumps.
- Internal pressure relief valves for overload protection.
- External load release valve for single-acting cylinder operation.
- Two-speed pump operation reduces handle strokes by as much as 78% over single speed pumps.
- Durable glass-filled nylon reservoir and nylon encapsulated aluminum pump base for maximum corrosion resistance and lightweight handling.
- Handle lock for easy carrying.
- Non-conductive fiberglass handle for operator safety.

Description

For many applications including shop, agricultural, automotive/truck service needs and construction maintenance applications where high pressure pumps are required to activate cylinders rated as high as 55 ton capacity

FEATURES:

- 3/8 NPT hose connection on all pumps.
- Internal pressure relief valves for overload protection.

- External load release valve for single-acting cylinder operation.
- Two-speed pump operation reduces handle strokes by as much as 78% over single speed pumps.
- Durable glass-filled nylon reservoir and nylon encapsulated aluminum pump base for maximum corrosion resistance and lightweight handling.
- Handle lock for easy carrying.
- Non-conductive fiberglass handle for operator safety.

Specifications

PSI (First Stage): 200

PSI (Second Stage): 10,000

Usable Oil Cap (Cu. In.): 55

Oil Displacement Per Stroke (Cu. In. First Stage): .687

Oil Displacement Per Stroke (Cu. In. Second Stage): .151

Max Handle Effort (Lbs.): 93

Piston Stroke (In.): 1.00

Length: 21.63"

Width: 4.75"

Height:7"

Pump Handle Arc: 50*

Weight: 9lbs.