72550B - NORCO - 1/2-Ton Telescopic Under-Hoist Double Pump Tran



Brand: Norco

Product Code: NOR-72550B Call for Price: 877-805-1154

Phone: 877-805-1154 - Email: parts@automotive-lift.com

Short Description

72550B - NORCO - 1/2-Ton Telescopic Under-Hoist Double Pump Trans. Fast Jack

Designed for the removal, installation and transportation (in the lowered position) of transmissions and transfer cases on passenger cars, vans and light trucks that are raised by an in-ground or above-ground lift.

FEATURES:

- U.S. Patent No. 5,975,496 (Double Pump Design)
- Fully adjustable universal saddle with hand adjustable corner brackets and safety chain.
- Safety overload system prevents jack from being used beyond its rated capacity.
- Foot operated pump and lowering pedals allow use of both hands to position and align saddle with transmission.
- Two-stage flash chromed rams inhibit rust from entering hydraulic system.
- Wide base with four easy rolling 4" diameter swivel ball bearing caster wheels provides stability and easy maneuvering in its lowered position. The polyurethane wheels provide protection for expensive tile and epoxy floors.

- Two times faster rising action as model <u>72500E</u> with no load or a load up to 400 pounds.
- Same rising action as model <u>72500E</u> for loads between 400 and 1,000 pounds.

Description

72550B - NORCO - 1/2-Ton Telescopic Under-Hoist Double Pump Trans. Fast Jack

Designed for the removal, installation and transportation (in the lowered position) of transmissions and transfer cases on passenger cars, vans and light trucks that are raised by an in-ground or above-ground lift.

FEATURES:

- U.S. Patent No. 5,975,496 (Double Pump Design)
- Fully adjustable universal saddle with hand adjustable corner brackets and safety chain.
- Safety overload system prevents jack from being used beyond its rated capacity.
- Foot operated pump and lowering pedals allow use of both hands to position and align saddle with transmission.
- Two-stage flash chromed rams inhibit rust from entering hydraulic system.
- Wide base with four easy rolling 4" diameter swivel ball bearing caster wheels provides stability and easy maneuvering in its lowered position. The polyurethane wheels provide protection for expensive tile and epoxy floors.
- Two times faster rising action as model <u>72500E</u> with no load or a load up to 400 pounds.
- Same rising action as model <u>72500E</u> for loads between 400 and 1,000 pounds.