

## 910140 - Norco 10,000 PSI 2-Gal Air/Hydraulic Foot Pump



**Brand:** Norco  
**Product Code:** NOR-910140  
**Call for Price:** 877-805-1154

### Short Description

For automotive / truck, industrial & construction jobs. The added convenience of an air motor reduces pumping time and effort to activate cylinders.

### FEATURES:

- Designed to utilize exhaust air to help power the pump, requiring only 80 p.s.i. air pressure to develop 10,000 p.s.i. hydraulic pressure.
- Air exhaust muffler for quieter operation.
- Air and oil inlet filters for reduced risk of damage from contamination.
- Designed with durable light weight, corrosion resistant plastics.
- Foot pedal provides hands free pumping and release of load.
- Designed to be used with a single-acting cylinder.
- Internal pressure relief valve for overload protection.
- Two-gallon capacity aluminum reservoir body.
- Comes with two different size poppit valves that can be quickly and easily installed. Poppit valves reduce the return flow of oil back to the pump's reservoir providing a safer controlled lowering of load.
- Equipped with a thick wall aluminum extruded reservoir.

## **Description**

For automotive / truck, industrial & construction jobs. The added convenience of an air motor reduces pumping time and effort to activate cylinders.

## **FEATURES:**

- Designed to utilize exhaust air to help power the pump, requiring only 80 p.s.i. air pressure to develop 10,000 p.s.i. hydraulic pressure.
- Air exhaust muffler for quieter operation.
- Air and oil inlet filters for reduced risk of damage from contamination.
- Designed with durable light weight, corrosion resistant plastics.
- Foot pedal provides hands free pumping and release of load.
- Designed to be used with a single-acting cylinder.
- Internal pressure relief valve for overload protection.
- Two-gallon capacity aluminum reservoir body.
- Comes with two different size poppit valves that can be quickly and easily installed. Poppit valves reduce the return flow of oil back to the pump's reservoir providing a safer controlled lowering of load.
- Equipped with a thick wall aluminum extruded reservoir.

## **Specifications**

P.S.I.: 10,000

Usable Oil Cap (Cu. In.): 462

Output Flow Rate with Load: 80.5

Output Flow Rate No Load: 12.8

P.S.I Range: 40-170

Air Consumption (scfm): 24

Valve Function: Advance/Hold/Retract

Sound Level (Dba): 85

Thread Connections (Air NPT): .25"-18

Thread Connections (Hydraulic NPT): .375"-18

Dimensions (Inches)

Length:14"

Width: 8.5"

Height:10.75"

Weight: 44