

925013B - Norco 350/10,000 PSI Two-Speed Steel Hand Pump



Brand: Norco
Product Code: NOR-925013B
Call for Price: 877-805-1154

Short Description

For many applications including shop, agricultural, automotive/truck service needs and construction maintenance applications where high pressure pumps are required to activate cylinders rated as high as 55 ton capacity

FEATURES:

- 3/8 NPT hose connection on all pumps.
- Internal pressure relief valves for overload protection.
- External load release valve for single-acting cylinder operation.
- Two-speed pump operation for reduced operator fatigue.

Description

For many applications including shop, agricultural, automotive/truck service needs and construction maintenance applications where high pressure pumps are required to activate cylinders rated as high as 55 ton capacity

FEATURES:

- 3/8 NPT hose connection on all pumps.
- Internal pressure relief valves for overload protection.

- External load release valve for single-acting cylinder operation.
- Two-speed pump operation for reduced operator fatigue.

Specifications

PSI (First Stage): 350

PSI (Second Stage): 10,000

Usable Oil Cap (Cu. In.): 134

Oil Displacement Per Stroke (Cu. In First Stage): .99

Oil Displacement Per Stroke (Cu. In. Second Stage): .15

Max Handle Effort (Lbs.): 104

Piston Stroke (In.): 1.00

Length: 22.5"

Width: 5.75"

Height: 7"

Pump Handle Arc: 50*

Weight: 24lbs.