

300T - AFF - 3 Ton Heavy-Duty Low Profile Double-Pumper Floor Jack



Brand: American Forge & Foundry
Product Code: AFF-300T
Call for Price: 877-805-1154

Short Description

300T - AFF - 3 Ton Heavy-Duty Low Profile Double-Pumper Floor Jack

AFF Floor Jacks are heavy duty and designed to meet the demanding lifting needs of the professional service technician. They have heavy gauge steel, flanged side plates for strength, UV powder coat paint, and safety overload valve for added protection. These are some of the strongest and most durable jacks in the industry.

Features:

- Super low pick up point of 3.75" (1/4" lower than 350SS)
- High height of 21.5" (2.0" higher than 350SS, 1.5" higher than 200T)
- Universal joint technology for precise release valve control
- Tough powder-coated frame for longer shop life
- Pinned steel saddle (1 1/8" stud) with rubber pad for added vehicle protection
- Safety valve to prevent overloading
- Plungers use a 'U' Cup design instead of O ring, for a better seal
- Centered pump plunger design offer 20% longer life over offset
- Release valve porting is designed for slower controlled descent
- Pump design engages sooner for longer stroke
- Tough powder coated frame for longer shop life

Description

300T - AFF - 3 Ton Heavy-Duty Low Profile Double-Pumper Floor Jack

AFF Floor Jacks are heavy duty and designed to meet the demanding lifting needs of the professional service technician. They have heavy gauge steel, flanged side plates for strength, UV powder coat paint, and safety overload valve for added protection. These are some of the strongest and most durable jacks in the industry.

Features:

- Super low pick up point of 3.75" (1/4" lower than 350SS)
- High height of 21.5" (2.0" higher than 350SS, 1.5" higher than 200T)
- Universal joint technology for precise release valve control
- Tough powder-coated frame for longer shop life
- Pinned steel saddle (1 1/8" stud) with rubber pad for added vehicle protection
- Safety valve to prevent overloading
- Plungers use a 'U' Cup design instead of O ring, for a better seal
- Centered pump plunger design offer 20% longer life over offset
- Release valve porting is designed for slower controlled descent
- Pump design engages sooner for longer stroke
- Tough powder coated frame for longer shop life

Specifications

Specifications:

- Capacity: 3 Tons
- Low Height: 3.75"
- High Height: 21.5"
- Chassis Length: 30.75"
- Overall Width (front): 11.375"
- Overall Length (rear): 14.5"
- Ship Weight: 104 LBS

PLEASE GIVE US CALL SO WE MAY PROVIDE YOU AN ACURATE SHIPPING QUOTE. AUTOMATED SYSTEM CANNOT PROVIDE ACURATE PRICING FOR SHIPMENTS WEIGHING OVER 100 LBS