

3700 - AFF - Clutch Jack

Brand: American Forge & Foundry

Product Code: AFF-3700

Call for Price: 877-805-1154



Short Description

3700 - AFF - Clutch Jack

AFF Clutch Jack Accessories are designed to assist in all aspects of clutch removal and transport. Accessories include various adapters that are available to make the Clutch Jack a "one-man" operation.

A highly efficient design that provides the technician with capabilities to remove, install and transport heavy duty truck clutches. This heavy duty unit has a greater capacity than most competitive units and has the added versatility of being able to convert the optional adapters for fly wheels, drive shafts, starter motors, auxiliary cases, differentials, brake drums and camel back springs

Features:

- Clutch head assembly turns 360° and pivots side-to-side for efficient clutch/engine alignment
- Two splined alignment shafts (2" OD x 1.18" pilot and 1-3/4" OD x .938" pilot)
- Clutch assemblies can easily be built on the vertical shaft and then positioned easily under the truck
- Pump handle rotates 360° for ease of operation in virtually any work position
- Unique clevis pinned alignment shaft allows technician to remove jack to install clutch assembly without obstruction

- Alignment shafts have "flats" for open end wrench to aid in clutch indexing and internally threaded for slide hammer removal if needed.

Description

3700 - AFF - Clutch Jack

AFF Clutch Jack Accessories are designed to assist in all aspects of clutch removal and transport. Accessories include various adapters that are available to make the Clutch Jack a "one-man" operation.

A highly efficient design that provides the technician with capabilities to remove, install and transport heavy duty truck clutches. This heavy duty unit has a greater capacity than most competitive units and has the added versatility of being able to convert the optional adapters for fly wheels, drive shafts, starter motors, auxiliary cases, differentials, brake drums and camel back springs

Features:

- Clutch head assembly turns 360° and pivots side-to-side for efficient clutch/engine alignment
- Two splined alignment shafts (2" OD x 1.18" pilot and 1-3/4" OD x .938" pilot)
- Clutch assemblies can easily be built on the vertical shaft and then positioned easily under the truck
- Pump handle rotates 360° for ease of operation in virtually any work position
- Unique clevis pinned alignment shaft allows technician to remove jack to install clutch assembly without obstruction
- Alignment shafts have "flats" for open end wrench to aid in clutch indexing and internally threaded for slide hammer removal if needed.

Specifications

Specifications:

- Capacity: 500 LBS
- Low Height: 13"
- High Height: 39"
- Frame Dimension: 36.5" L x 22" W
- Ship Weight: 138 LBS

PLEASE GIVE US CALL SO WE MAY PROVIDE YOU AN ACURATE SHIPPING QUOTE. AUTOMATED SYSTEM CANNOT PROVIDE ACURATE PRICING FOR SHIPMENTS WEIGHING OVER 100 LBS